

UL INTERNATIONAL (UK) LTD Wonersh House, Building C, The Guildway, Old Portsmouth Road, Guildford. GU3 1LR. United Kingdom.





designated according to Article 29 of the Regulation (EU) No 305/2011 and member of EOTA (European Organisation for Technical Assessment, www.eota.eu)

European Technical Assessment

ETA 17/0218 of 01/03/2017

Technical Assessment Body issuing the ETA and designated according to Article 29 of the Regulation (EU) No 305/2011: UL International (UK) Ltd

Trade name of the construction product

Seals A Premium Acryl Kit

Product family to which the construction product belongs

Fire Stopping and Sealing Product:Linear Joint and Gap Seals

~() <

Manufacturer

FireCare Brandwerende Technieken B.V.

loge Vaa

396 Ne Vij bij Duurstede

The Netherlan

Manufacturing plant(s)

A/003

This European Technical Assessment contains

This European Technical Assessment is issued in accordance with regulation (EU) No 305/2011, on the basis of

9 pages including 1 Annex which forms an integral part of this assessment.

ETAG 026-3 edition 2011, used as European Assessment Document (EAD)

Translations of this European Technical Assessment in other languages shall fully correspond to the original issued document and should be identified as such.

Communication of this European Technical Assessment, including transmission by electronic means, shall be in full. However, partial reproduction may be made, with the written consent of the issuing Technical Assessment Body. Any partial reproduction has to be identified as such.

Table of Contents

1 Technical description of the product	I. S	PECIFIC PARTS OF THE EUROPEAN TECHNICAL ASSESSMENT
Document (Hereinafter EAD): ETAG 026-3	1	Technical description of the product
ASSESSMENT AND VERIFICATION OF CONSTANCY OF PERFORMANCE (HEREINAFTER AVCP) SYSTEM APPLIED, WITH REFERENCE TO ITS LEGAL BASE Technical details necessary for the implementation of the AVCP system, as provided for in the applicable EAD Sisued on: ANNEX A – Resistance to Fire Classification – Seals A Premium Acryl Kit Flexible wall constructions according to 1.2.1 with wall thickness of minimum 100 mm 7 A.1.1 Linear joint seals, between head of flexible wall and soffit of concrete floor and vertical end of flexible wall and concrete wall A.2.1 Rigid wall constructions according to 1.2.1 with wall thickness of minimum 150 mm 8 A.3.1 Rigid floor constructions according to 1.2.1 with floor thickness of minimum 150 mm Significant or gap seal, between head of rigid wall and soffit of concrete floor / between rigid walls Significant or gap seal, between head of rigid wall and soffit of concrete floor / between rigid walls Significant or gap seal, between head of rigid wall and soffit of concrete floor / between rigid walls Significant or gap seal, between head of rigid wall and soffit of concrete floor / between rigid walls Significant or gap seal, between head of rigid wall and soffit of concrete floor / between rigid walls Significant or gap seal, between head of rigid wall and soffit of concrete floor / between rigid walls Significant or gap seal, between head of rigid wall and soffit of concrete floor / between rigid walls Significant or gap seal, between head of rigid wall and soffit of concrete floor / between rigid walls Significant or gap seal, between head of rigid wall and soffit of concrete floor / between rigid walls Significant or gap seal, between head of rigid wall and soffit of concrete floor / between rigid walls Significant or gap seal, between head of rigid wall and soffit of concrete floor / between head of rigid wall and soffit of concrete floor / between head of rigid wall and soffit of concrete floor / between head of rigid wall and soffit of concrete floor / between head of rig	2	·
APPLIED, WITH REFERENCE TO ITS LEGAL BASE	3	Performance of the product and references to the methods used for its assessment4
EAD	4	
ANNEX A – Resistance to Fire Classification – Seals A Premium Acryl Kit	5	
A.1 Flexible wall constructions according to 1.2.1 with wall thickness of minimum 100 mm	6	Issued on:
A.1.1 Linear joint seals, between head of flexible wall and soffit of concrete floor and vertical end of flexible wall and concrete wall	ANNE	X A – Resistance to Fire Classification – Seals A Premium Acryl Kit
wall and concrete wall	A.1	Flexible wall constructions according to 1.2.1 with wall thickness of minimum 100 mm
A.2.1 Linear joint or gap seal, between head of rigid wall and soffit of concrete floor / between rigid walls8 A.3 Rigid floor constructions according to 1.2.1 with floor thickness of minimum 150 mm	A.1.1	·
A.3 Rigid floor constructions according to 1.2.1 with floor thickness of minimum 150 mm9	A.2	Rigid wall constructions according to 1.2.1 with wall thickness of minimum 150 mm
	A.2.1	Linear joint or gap seal between head of rigid wall and soffit of concrete floor / between rigid walls
A.3.1 Linear joint or gap seal, between floor slabs or between floor slab and wall with sealant to the top face of the floor only	A.3	
	A.3.1	Linear joint or gap seal, between floor slabs or between floor slab and wall with sealant to the top face of the floor only